

# TECHNICAL DATA SHEET

## DOZER S3 SRC ESD

### Safety shoes

Article NO: G3213

Upper: nubuck leather/textile

Sole: PU/ PU

Description: ankle shoes with laminate toe cap, flexible kevlar insole

Size: 36 - 48



Ankle shoes with laminate toe cap, flexible kevlar insole. Black colour, no metal parts. Flexible kevlar insole protects the entire area of the foot. ESD anti-static shoes protects electrostatically sensitive components from electrostatic discharges and fields.

### Type and degree of protection:

| Category  | EN ISO 20345 |
|---|--------------|
| Antistatic properties   | X            |
| Absorption of energy in the heel area   | X            |
| Sole with pattern- oil resistance   | X            |
| Water resistance  | X            |
| Puncture resistance (kevlar insole)   | X            |
| Laminate safety toecap for toe protection   | X            |
| Without metal parts   | X            |
| Slip resistant ceramic tile floor with SLS and on steel floor with glycerol (SRC) | X            |
| ESD antistatic shoes  | X            |



This personal protective equipment is in conformity with this harmonized European



Standard:

EN ISO 20345:2011 : Personal protective equipment - safety shoes.

EN ISO 61340-4-3:2001 : Electrostatics - Part 4-3: Standard test methods for specific applications - Shoes

Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol (SRC mark).

Certified by notified body no. 2474 (Mirta Kontrol, Javorinska 3, HR-10040 Zagreb - Dubrava, Hrvatska) - dated 03<sup>rd</sup> November 2021, certificate no. OZO311-CPT001/21.

---

|                  |                      |
|------------------|----------------------|
| Pairs in carton: | 10                   |
| Carton weight:   | 18,46 kg             |
| Carton size:     | 0,123 m <sup>3</sup> |

---

The shoes have to be perfect as for form and size, because they have rigid parts. The right size has to be found by measuring practically and carefully the shoes. The closing system has to be used correctly. The laces have to be tightened well without leaving too long free tops. The shoes have to be cleaned and treated with right, specific products, following the instructions for use. Do not keep footwear near heatings when not used and let them dry in a windy or room temperature. Before wearing and when cleaned, the shoes have to be controlled in order to find out visible defects existing, like closing system function, outsole profile's water, possible damages, etc. To define the right type of footwear to wear in every environment, the possible dangers and the place/ environment have to be included (e.g. construction industry, high temperatures, etc.). The shoes have to be stored correctly, keeping them in the proper packing.

---