

TECHNICAL DATA SHEET

VISION 03

Workwear

Article NO: H9105 (black)

H9108 (grey) H9111 (tarmac)

H9144 (tarmac extended) H9147 (tarmac shortened)

Outshell: twill 60% cotton, 40% polyester

Grammage: 260 g/m²

Size: 46 - 64

Bibpants made from quality mixed material.

Description: bib with pockets, elastic braces, reinforced knees, pockets for knee pads, pockets and loops for tools

This personal protective equipment is in conformity with these harmonized European Standards:

ČSN EN ISO 13688:2013: Protective cloathes - General requirements.

PPE of the simply construction against minimal risk, which can be recognized by the user early and safely.

Self certification have been performed on the base of technical documentation of the PPE and practical exams of the ergonomic features of the PPE by the Voženílek pracovní ochranné pomůcky s.r.o. company, dated 22nd January 2014.

Collection VISION meet the requirements for medical harmlesness and is holder of the certificate of OEKO-TEX®Standard 100, certificate no. PG020128167.



www.oeko-tex.com/standard100

Pieces in carton: 10
Carton weight: 24,0 kg
Carton size: 0,085 m³

Polybag packing (pieces): 1

Service life depends on the frequency of use and the wear rate under the given conditions. Improper storage and improper maintenance and handling will reduce the service life. The warranty period is



24 months. In no event may the warranty period be confused with a product's service life. Under intense use, the service life may be shorter than the warranty period.

The product contains no substances at concentrations that are known or suspected to have adverse effects on sanitation or a user's health. However, skin irritation may occur with sensitive persons; in this case, the discontinue use of the clothing. Avoid fire and intense heat sources. There are no designated accessories or spare parts for this clothing. When a garment is not being worn, it should be stored in dry and well ventilated places out of direct sunlight. In order to transport, the original packaging should be used. Protect from moisture and extreme temperatures. After use, dispose of in an environmentally friendly manner.