



TECHNICAL DATA SHEET

MASTERLOW O2 SRC

Working shoes

Article NO: G3288

Upper: buffalo leather

Sole: PU/PU

Size: 36 - 48



Leather low shoes, water resistant.

Type and degree of protection:

Category	EN ISO 20347
Antistatic properties	x
Absorption of energy in the heel area	x
Sole with pattern- oil resistance	x
Water resistance	x
Slip resistant ceramic tile floor with SLS and on steel floor with glycerol (SRC)	x



This personal protective equipment is in conformity with this harmonized European Standard:

EN ISO 20347:2012 : Personal protective equipment - Working shoes.

Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol (SRC mark).

Certified by notified body no. 2474 (MIRTA-KONTROL d.o.o., Gradiška 3, HR-10040 Zagreb - Dubrava, Croatia), Certificate number OZO311-CPT004/19.

Pairs in carton: 10
Carton weight: 16,4 kg
Carton size: 0,069 m³



The shoes have to be perfect as for form and size, because they have rigid parts. The right size has to be found by measuring practically and carefully the shoes. The closing system has to be used correctly. The laces have to be tightened well without leaving too long free tops. The shoes have to be cleaned and treated with right, specific products, following the instructions for use. Do not keep footwear near heatings when not used and let them dry in a windy or room temperature. Before wearing and when cleaned, the shoes have to be controlled in order to find out visible defects existing, like closing system function, outsole profile's water, possible damages, etc. To define the right type of footwear to wear in every environment, the possible dangers and the place/ environment have to be included (e.g. construction industry, high temperatures, etc.). The shoes have to be stored correctly, keeping them in the proper packing.
