

## TECHNICAL DATA SHEET

### V6200


#### Eye protection

Article NO: E4031


Lens: yellow  
 Material- lens: polycarbonate  
 Material- temples: nylon



Stylish safety glasses which combine fashionable look, comfort and functionality. Soft orange groove temples tips make the temples fit perfectly without sliding. Adjustable temples tilt enables the glasses to adapt to the shape of the face easily. Large yellow polycarbonate lens which are made from one piece protect against UV radiation and have a function of anti-solar filter while maintaining adequate color perception. They are anti-fogging, anti-scratching and resistant to low-energy shocks (up to 45 m/s) at extreme temperatures (-5 °C - +55 °C) and provide maximum protection.



Adjustable temple length - YES



Adjustable temple angle - YES



Anti-fogging lens - YES



Anti-scratching lens - YES

#### Yellow lens, UV, 2-1.2 1 FT 0

Type of filter:	2	UV filter
Shade number:	1.2	yellow
Optical class:	1	permanent use
Mechanical resistance:	FT	resistant to low-energy shocks at extreme temperatures
Type of the lens:	0	original lens



This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001 : Personal eye protection. General requirements.

Certified by notified body no. 2797 (BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands),  
Certificate no CE 692741, dated 12<sup>th</sup> September 2019.

---

Pieces in carton:	250
Pieces in box:	10
Polybag packing (pieces):	1
Carton weight:	13 kg
Carton size:	0,103 m <sup>3</sup>

---

Store in dry and dark environment away from direct sunlight at temperatures of -5 °C to +55 °C, relative humidity 90% and out of sources of gasoline vapors and solvents.  
It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.

---